



## 4th Generation Dry Cleaning Machines

The most advanced design from Germany's dry cleaning industry, manufactured to the highest standard with stainless steel throughout, including the base tanks.

### Efficiency:

The highest level of efficiency is achieved by these 4th generation machines.

- Faster drying.
- Energy saving.
- Increased environmental safety.

### Features:

- Three solvent tanks.
- Single centrifugal filter with optional second filter.
- Computer controlled, fully automatic with manual override.
- Famous brand refrigeration system.
- Carbon absorbing OSHA fan.
- Available with electric or steam heating.
- Available with optional inverter drive.
- Optional "Arctic" solvent cooling system.





## SEVE Dry Cleaning Machines

	Unit	M7	M9	M11	M13	M16	M18	M20	M25	M30
Capacity	kg	7	9	11	13	16	18	20	25	30
Volume	L	140	180	220	260	320	360	400	500	600
Washer Speed	rpm	34	34	34	34	34	34	34	34	34
Extraction Speed	rpm	370	370	370	370	370	370	370	370	370
Tanks	pcs	3	3	3	3	3	3	3	3	3
<b>Machine Dimensions</b>										
Depth	mm	1500	1500	1500	1550	1550	1600	1600	1700	1750
Width	mm	1850	1850	1850	1950	1950	2100	2220	2270	2350
Height	mm	2040	2040	2040	2200	2200	2200	2300	2300	2350
Weight without Solvent	kg	800	850	950	1000	1100	1150	1200	1400	1800
<b>Power Requirement</b>										
Electric Heated	kw	12.75	13.5	13.5	13.5	15.5	15.5	15.5	18.5	25
<b>Supply Connections</b>										
Compressed Air Flow	m <sup>3</sup> / min	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
Compressed Air Pressure	kg / cm <sup>2</sup>	4.5	4 - 5	4 - 5	4 - 5	4 - 5	4 - 5	4 - 5	4 - 5	4 - 5
Compressed Air Fittings	mm	8	8	8	8	8	8	8	8	8
Steam Pressure	kg / cm <sup>2</sup>	4 - 6	4 - 6	4 - 6	4 - 6	4 - 6	4 - 6	4 - 6	4 - 6	4 - 6
Steam Consumption	kg / hr	30	32	34	36	40	42	44	49	57
Steam Fittings	inch	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"
Condensate Outlet	inch	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"	2x1/2"
Water Consumption	kg / hr	400	450	500	550	580	600	620	700	950
Water Pressure	kg / cm <sup>2</sup>	2 - 3	2 - 3	2 - 3	2 - 3	2 - 3	2 - 3	2 - 3	2 - 3	2 - 3
Size of Fittings - Inlet/Outlet	inch	1 "	1 "	1 "	1 "	1 "	1 "	1 "	1 "	1 "
Electrical Requirement	V/Ph/Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50

E & OE. Models and specifications subject to change without prior notice.

