

Professional Range

The SEVE Professional Range of Washer Extractors and Dryers is designed to meet the needs of small laundries: Ideal for Laundromats, Boutique Hotels, Clinics, Spas, Salons, Clubs, Hostels. Small capacity but brilliant performance, efficient, versatile, space saving + long lifespan.



PW 8-10-12



PD 8-10-12



PWD 8-10-12



PDS 8-10-12

Features:

- Heavy duty fully stainless steel construction
- Easy to program simple computer
- Inverter drive running one motor
- High aspect ratio of drum design
- Washer has variable extraction speeds
- Automatic chemical dosing
- Can be fitted with auto liquid dosing
- Dryers have stainless steel drums
- Dryers have reversing drum action
- Hard mount design
- Electric, Steam or Gas heating
- All models can be token operated

Benefits:

- Low maintenance & long service life
- Fully auto programs for all requirements
- Energy efficiency and reduced stress
- Uses less water, chemicals, heating
- Maximum flexibility
- Labour saving
- Maximizes chemical efficiency
- No possibility of rust marks
- Improved drying efficiency and no tangling
- Easy to mount to a concrete floor.
- Can be used "off the grid"
- Ideal for Laundromats and security control





| | PW 8-10-12 | PD 8-10-12 | PWD 8-10-12 | PDS 8-10-12 |
|--------------------------------------|--------------------|--------------------|-------------------------|--------------------|
| Rated Dry mass Capacity kg | 8 / 10 / 12 | 8 / 10 / 12 | 8 / 10 / 12 | 8 / 10 / 12 |
| Cylinder Size mm 8 Kg Model | ø 580 x 310 | ø 680 x 450 | | |
| Cylinder Size mm 10 Kg Model | ø 580 x 380 | ø 680 x 570 | | |
| Cylinder Size mm 12 Kg Model | ø 580 x 460 | ø 680 x 680 | | |
| Washing Speed rpm | 45 | 45 | | |
| Extraction Speed rpm | 500 - 800 | | | |
| Motor Power kw | 0.75 / 1.1 / 1.5 | 0.74 | 0.75 / 1.1 / 1.5 + 0.74 | 1.48 |
| Element Power kw | 7.5 / 9 / 12 | 8 / 10 / 12 | 15.5 / 19 / 24 | 16 / 20 / 24 |
| Steam consumption kg per cycle | 8 / 10 / 12 | 12 / 15 / 18 | 20 / 25 / 30 | 24 / 30 / 36 |
| Gas consumption kg per cycle | 0.85 / 1.05 / 1.25 | 0.85 / 1.05 / 1.25 | 1.7 / 2.1 / 2,5 | |
| Water consumption M3 | 1.6 / 2.0 / 2.4 | 1.6 / 2.0 / 2.4 | | |
| Dimensions W: D: H mm 8 Kg Model | 750 / 980 / 1100 | 740 / 920 / 1220 | 800 / 940 / 2150 | 740 / 920 / 2440 |
| Dimensions W: D: H mm 10 Kg Model | 750 / 1050 / 1100 | 740 / 1040 / 1220 | 800 / 1060 / 2150 | 740 / 1040 / 2440 |
| Dimensions W: D: H mm 12 Kg Model | 750 / 1130 / 1100 | 740 / 1150 / 1220 | 800 / 1170 / 2150 | 740 / 1150 / 2440 |

E & OE. Models and specifications subject to change without prior notice.

