



SEVE XGQ - F Series of Soft Mounted High Speed Washer Extractors





SEVE washer extractors are high quality machines fitted with the latest modern features. They have easy to use fully programmable computer controls with an inverter drive running one motor and are very efficient in the use of energy, water and chemicals due to the excellent aspect ratio of the drum and sump design. The extraction speeds are variable. They can be fitted with automatic liquid chemical dosing systems.

Features:

- Programmable computer control with clear display.
- Automatic testing to track down the operating condition in time.
- Advanced frequency conversion and speed-adjusting system.
- Suspension and shock absorption system to minimise noise and shock.
- All models fitted with inverter drive.
- Heavy duty fully stainless steel construction.
- Alternative hard mounted models available from 12kg to 55kg.



Inner drum



35 F - 150 F Computer



15 F - 23 F Computer





SEVE XGQ - F Series Models

	Unit	XGQ 150 F	XGQ 120 F	XGQ 100 F	XGQ 80 F	XGQ 55 F	XGQ 35 F	XGQ 23 F	XGQ 15 F
Rated Load	kg	150	120	100	80	55	35	23	15
Cylinder Size	mm	∅ 1320*1100	∅ 1220*1030	∅ 1220*860	∅ 1220*690	∅ 955*700	∅ 940*500	∅ 750*540	∅ 750*340
Washing Speed	rpm	32	33	33	33	36	36	38	38
Extraction Speed	rpm	340 - 750	340 - 800	340 - 800	340 - 800	340 - 850	340 - 850	340 - 850	340 - 900
Motor Power	kw	22	18.5	15	11	7.5	5.5	3	2.2
Element Power	kw	N/A	N/A	N/A	N/A	36	24	21	15
Machine Dimensions									
Width	mm	1950	1850	1850	1850	1600	1350	1260	1260
Depth	mm	2100	2040	1860	1690	1590	1350	1270	1110
Height	mm	2100	2030	2030	2030	1710	1650	1540	1540
Mass	kg	4500	3300	3000	2500	1600	1350	1000	700
Consumption Per Cycle									
Electricity Consumption	kw / hr	4.5	3.4	3.1	2.8	12.1	8.75	7.5	5.25
Steam Consumption	kg	130	100	85	70	50	35	25	15
Water Consumption	m ³	2.0	1.5	1.3	1.1	0.6	0.5	0.4	0.35

E & OE. Models and specifications subject to change without prior notice.

