



SERVICE | EXCELLENCE | VALUE | EFFICIENCY

XGQ-Series

XGQ-Series Washer Extractor

The XGQ Series is the choice for operations that value long-term energy efficiency and reduced operating costs. The suspended soft-mount design requires no reinforced concrete plinth — faster installation, no civil works costs and the flexibility to install on any floor. With extraction forces above 300G, less water in the load means shorter drying cycles, lower heating energy costs and less wear on your drying equipment. Inverter-driven motors consume only the power each load demands. The smart long-term investment for hotels, hospitals, and commercial laundries.

Key Features

- Simple to operate — programmable controls, no specialist training needed.
- Energy efficient — inverter drive uses only the power each load demands
- Quiet operation — suspension system minimises noise and vibration
- No civil works — installs on any floor, no concrete plinth needed
- Stainless steel throughout - panels, inner and outer drums built for harsh detergents and high humidity.
- 5 chemical ports — allow for precise automatic chemical dosing

Essential Data

- | | |
|-------------------|-----------------------------------|
| • Colour: | Stainless Steel |
| • Capacity (kg): | 15, 25, 35, 55, 80, 100, 120, 150 |
| • Heating Source: | Electric or Steam |
| • Power Supply: | 380V/50Hz/3N |
| • Warranty: | 1-Year |



Technical Specifications

Models	XGQ15	XGQ25	XGQ35	XGQ55	XGQ80	XGQ100	XGQ120	XGQ150
Rated Load (kg)	15	25	35	55	80	100	120	150
Cylinder Size	438 x Ø660	540 x Ø750	500 x Ø940	700 x Ø955	690xØ1220	860xØ1220	1030xØ1220	1100xØ1320
Wash Speed (rpm)	48	38	36	36	33	33	33	32
Extraction Speed (rpm)	1000	850	750	750	670	670	670	660
Motor Power (kW)	1.5	3	5.5	7.5	11	15	18.5	22
Heating Power (kW)	9	21	27	36	-	-	-	-
Water Inlet (in)	¾	1	1	1	1.5	1.5	1.5	1.5
Drain Outlet (mm)	Ø75	Ø75	Ø75	Ø75	Ø140	Ø140	Ø140	Ø140
CONSUMPTION PER CYCLE *								
Water (l)	92	149	207	314	377	444	530	662
Electricity (kW)	2.58	3.6	5.06	6.8	2.6	3.55	4.37	5.2
Steam (kg)	11	15	22	30	52	60	75	97
DIMENSIONS								
Width (mm)	880	1270	1350	1530	1670	1840	2040	2120
Height (mm)	1413	1540	1540	1540	1700	1700	2030	2030
Depth (mm)	858	1220	1440	1440	1850	1850	1850	1950
Net Weight (kg)	360	1000	1500	1700	2850	3150	3500	4100

*Cold water temp. 15°C and hot water temp. 60°C. Full load. 45 minutes.

Due to continuous product improvements, design and specifications are subject to change without prior notice. E & OE.