



SERVICE | EXCELLENCE | VALUE | EFFICIENCY

HS-Series Washer

HS-Series Washer Extractors

The SEVE HS Series is built for operations where the condition of every towel, sheet and garment reflects directly on the quality of the service they deliver, and where lower drying costs on every cycle go straight to the bottom line. Available in seven models from 18kg to 100kg, the HS Series delivers 300G extraction with soft-mount installation flexibility. A 7-inch touchscreen controller, 3D honeycomb drum technology, triple-sealed bearing system and intelligent balance protection make it the highest specified machine in the SEVE range. No concrete plinth required — install on any floor, in any building. Front-tilt models available on HS60T and HS100T. The benchmark in soft-mount washing technology.



Key Features

- IP65-rated controller - splash and dust proof for demanding laundry environments
- 3D honeycomb inner drum - better detergent penetration and reduced linen wear
- Perforated drum lifters - continuous shower action for superior wash and rinse results.
- 7" full-colour touchscreen - 50 programs.
- Triple-sealed bearing design - permanently lubricated and maintenance free.
- 95% vibration absorption — multi-point suspension runs quietly and vibration-free.
- Intelligent balance protection — mitigates load imbalance during high-speed extract.

Essential Data

- | | | | |
|-------------------|------------------------------|-----------------|---------------|
| • Colour: | Silver | • Power Supply: | 380v/50Hz/3Ph |
| • Capacity (kg): | 18, 23, 40, 60, 80, 100, 120 | • Warranty: | 1-Year |
| • Heating Source: | Electric or Steam | | |

Technical Specifications

Models	HS18	HS23	HS40	HS60	HS80	HS100	HS120
Rated Load (kg)	18	23	40	60	80	100	120
Cylinder Size	504 x Ø683	489 x Ø774	626 x Ø903	656 x Ø1078	673xØ1240	840xØ1240	816xØ1310
Extraction G-Force (G)	300	300	300	300	300	300	350
Extraction Speed (rpm)	1024	962	771	706	658	658	691
Motor Power (kW)	1.8	3	4	5.5	5.5	7.5	11
Heating Power (kW)	18	18	30	30	45	60	60
Water Inlet (in)	½	¾	2 x 1	2 x 1½	2 x 1½	2 x 1½	2 x 2
Steam Inlet (in)	½	½	¾	1	1	1	1
Drain Outlet (mm)	Ø51	Ø76	Ø76	Ø110	Ø110	2 x Ø110	2 x Ø125
Tilt Function	x	x	x	x	x	O	O
Stainless Steel Drum	✓	✓	✓	✓	✓	✓	✓
DIMENSIONS							
Width (mm)	900	1012	1180	1487	1672	1672	1774
Height (mm)	1307	1485	1520	1860	1986	1986	2092
Depth (mm)	1030	1070	1399	1482	1581	1748	1828
Net Weight (kg)	400	610	1140	1840	2100	2600	3170

Due to continuous product improvements, design and specifications are subject to change without prior notice. E & OE.